## 14 — GEO-INFORMATICS

(Answer ALL questions)

- 56. According to Stefan-Boltzman law, total radiant exitance from the surface of a material is directly proportional to
  - 1. Absolute temperature of the material
  - 2. Square of absolute temperature of the material
  - 3. Cube of absolute temperature of the material
  - 4. Fourth power of absolute temperature of the material
  - 57. The maximum spectral radiant exitance from earth features occurs at a wavelength of
    - 1. about 0.7 μm
    - 2. about 1.7 μm
    - 3. about 9.7 μm
    - 4. about 19.7 μm
  - 58. Sky appears in blue colour due to
    - 1. Selective scattering
    - 2. Mie scattering
    - 3. Surface scattering
    - 4. Non-selective scattering
  - 59. Plant reflectance in the range of 0.7 to 1.3  $\mu m$  results generally from the
    - 1. Water content in the plant
    - 2. Cell structure of the plant
    - 3. Age of the plant
    - 4. Chlorophyll in the plant
  - 60. The wavelength range of near-IR waves is
    - 1. 0.4-0.7 μm
    - 2. 0.7-1.3 μm
    - 3. 1.0-5.7 μm
    - 4. 1.4-15 μm

- 61. The most important source of electromagnetic radiation in passive remote sensing is
  - 1. Moon
  - 2. Earth
  - 3. Space
  - 4. Sun
- 62. The most often used signature in optical-IR remote sensing is
  - 1. Spectral variation
  - 2. Seasonal variation
  - 3. Earth rotation variation
  - 4. Satellite position variation
- 63. The orbital period of geo-synchronised satellite is
  - 1. One sidereal day
  - 2. One solar day
  - 3. 28 sidereal days
  - 4. 28 solar days
- 64. Earth remote sensing satellites are mostly
  - 1. Geo-synchronised satellites
  - 2. Sun synchronized satellites
  - 3. Geo-stationery satellites
  - 4. Geo-synchronised, sun synchronized and geo-stationery satellites
- 65. Which of the following scale of measurement may be used to represent area?
  - 1. Interval
  - 2. Ratio
  - 3. Nominal
  - 4. Ordinal

- Which one of the following is not a raster 71. Point-in-polygon overlay method can be used 66. data structure?
  - 1. Run-length encoding
  - 2. Spaghetti
  - 3. Quadtree
  - 4. Block encoding
- 67. The XML-based universal data standard recommended by the Open GIS Consortium is
  - 1. NTF
  - 2. HTML
  - 3. GML
  - 4. SDTS
- 68. Which of the following might be considered as the fourth dimension in GIS?
  - Location 1.
  - 2. Scale
  - Space 3.
  - Time 4.
- 69. Reclassification is defined as
  - 1. The process of combing two or more data layers
  - 2. The process of simplifying data in a data layer
  - 3. The process of combining one or more data ranges into a new data range to create a new data layer
  - 4. An analytical technique based on point data
- 70. Which of the following overlay methods would you use to calculate the length of road within a forest polygon?
  - 1. Erase
  - 2. Line-in-polygon
  - 3. Point-in-polygon
  - Union 4.

- - 1. Interpolate point data
  - 2. Determine the distance between a point and its nearest neighbouring polygon
  - 3. Determine which points lie within the boundary of a polygon
  - Reclassify polygon data 4.
- 72. Aspect is defined as
  - The direction of the fall line relative to 1. the line of greatest slope
  - 2. The direction of the fall line relative to north
  - 3. The percentage gradient of this line averaged over its full distance
  - 4. The gradient of the fall line
- The two important parameters obtained from 73. remote sensing for operational fisheries forecast are
  - Upwelling and salinity 1.
  - 2. SST and amount of chlorophyll
  - 3. Ocean currents and wind speed
  - 4. Primary and secondary productivity
- 74. The scale of is used for preparing national or state level land cover/land use maps
  - 1. 1:15
  - 2. 1:250000
  - 3. 1:50000
  - 4. 1:25000

- 75. Which of the following sensor is widely used for study about the Himalayan snow cover?
  - 1. CARTOSAT
  - 2. QUICKBIRD
  - 3. KALPANA
  - 4. MODIS
- 76. (Green reflectance SWIR reflectance)/
  (Green reflectance + SWIR reflectance) =
  - 1. NDSI
  - 2. NDVI
  - 3. EVI
  - 4. GARI
- 77. The movement of the projector in y-direction introduces in the model a y-parallax
  - 1. Maximum at position 5 and 6
  - 2. Minimum at position 5 and 6
  - 3. Equally throughout the model
  - 4. Maximum at position 3 and 4
- 78. The point where a vertical line through the optical center of the camera lens intersects the ground is known as
  - 1. Ground principal point
  - 2. Ground plumb point
  - 3. Ground perspective center
  - 4. Ground isocenter
- 79. An aerial photograph may be assumed as
  - 1. Central projection
  - 2. Conical projection
  - 3. Parallel projection
  - 4. Orthogonal projection

- 80. The scale of the photography taken from a height of 3000 m with a camera of focal length 150 mm is
  - 1. 1:5,000
  - 2. 1:50,000
  - 3. 1:2,000
  - 4. 1:20,000
- 81. The flying height of the camera is 1000 m above mean ground level, the distance of the top of a tower from a nadir point is 100 mm and the relief displacement is 7.2 mm. The height of the tower is
  - 1. 72 m
  - 2. 82 m
  - 3. 62 m
  - 4. 52 m
- 82. What does 1 mm on a map drawn at a scale of 1:50,000 represent on the ground?
  - 1. 500 centimetres
  - 2. 50 centimetres
  - 3. 50 metres
  - 4. 5 metres
- 83. Which of the following is not a type of map projection?
  - 1. Conic
  - 2. Azimuthal
  - 3. Geographic
  - 4. Cylindrical
- 84. Map Projections attempt to correct for errors in
  - 1. Area, Distance, Scale and Proportion
  - 2. Area, Distance, Shape and Direction
  - 3. Distance, Proximity, topology
  - 4. Distance, Shape and Lines of Latitude and Longitude

- 85. To a Cartographer 1:250,000 is a
  - 1. Small Scale
  - 2. Large Scale
  - 3. Medium Scale
  - 4. Low Scale
- 86. What type of map is most commonly used to map temperature data?
  - 1. Dot
  - 2. Flow
  - 3. Isothermic
  - 4. Choropleth
- 87. The basic principle of surveying is to work from
  - 1. Part to the whole
  - 2. Whole to the part
  - 3. Higher level to lower level
  - 4. Lower level to higher level
- 88. A final route will be selected based on the
  - 1. Detailed survey
  - 2. Location survey
  - 3. Preliminary survey
  - 4. Reconnaissance survey
- 89. Reciprocal ranging is used when alignment is to be done across
  - 1. A big river
  - 2. A pond
  - 3. A tall building
  - 4. Two stations when there is no intervisibility
- 90. Buildings are set on the ground by
  - 1. The inner line of each wall
  - 2. The outer line of each wall
  - 3. The central line of each wall
  - 4. The inner and outer line of each

- 91. O<sub>1</sub>, O<sub>2</sub>, O<sub>3</sub> are three consecutive offsets at common distance 'd' apart. The area of the strip by Simpson's rule is
  - 1.  $d/3 (O_1 + O_2 + O_3)$
  - 2.  $d/3 (O_1 + 2O_2 + O_3)$
  - 3.  $d/3 (O_1 + 3O_2 + O_3)$
  - 4.  $d/3 (O_1 + 4O_2 + O_3)$
- 92. The dip of the magnetic needle at the equator will be
  - 1. towards north pole
  - 2. towards south pole
  - 3. towards east / west
  - 4. neutral
- 93. The method by which an instrument station is established with reference to two points already plotted on the drawing paper is called
  - 1. Radiation
  - 2. Intersection
  - 3. Resection
  - 4. Triangulation
- 94. Survey that deals with the measurements in vertical planes is
  - 1. Horizontal survey
  - 2. Vertical survey
  - 3. Inclined survey
  - 4. Levelling
- 95. The technique used for reducing the speckle without losing spatial detail
  - 1. Moving window filters
  - 2. Multi-looking
  - 3. Temporal averaging
  - 4. Frequency filters

96.	Frequency adopted for RISAT data?	101. The very first polarimetric mission designed
30.	1. 5.36 GHz	is 'man distance that
	2. 23.5 GHz	1. SIR A
	3. 13.6 GHz	2. SIR B
	4. 1.3 GHz	3. SIR C
	1. 1.0 GHZ	4. RISAT
97.	The constructive and destructive interference from the multiple scattering returns that	102. ISODATA stands for
	occur within each resolution cell is called	1. Iterative Self-Organizing Data
	1. Surface roughness	Analysis Technique
	2. Speckle	2. Interactive Self-Organizing Data
	3. Volume scattering	Analysis Technique
	4. None of the above	3. Interpolating Organizing Data Analysis Technique
98.	The first experimental space borne SAR	4. Information Organizing Data Analysis Technique
	programme  1. JERS-1	
	2. ERS-1	103. Command used for correcting the sliver
	3. SEASAT-A	polygons
		1. Identity
	4. RADARSAT-1	2. Eliminate
99.	NISAR is expanded as	3. Rubber sheeting
00.	NASA-ISRO Synthetic Aperture Radar	4. Masking
	2. NASA-Indian Synthetic Aperture	
	Radar	104. End member in hyper spectral remote
	3. NASA Interferometric Synthetic	sensing is
	Aperture Radar	1. Pure Pixel
	4. NASA Indian Space Atmospheric	2. Mixed Pixel
	Radar	3. Linear Pixel
		4. Non linear pixel
100	). Scatterometers are used to measure the	
	based on the	105. In principal component transformation of
	backscattering principle  1. Near surface winds and bragg	image the first principal component mostly
		refers to
	2. Winds 10 meter above the sea surface and Facet	1. Overall noise
	3. Surface winds and Clapp	2. Overall brightness
	4. Winds 6 meter above the sea surface	3. Spatial variation
	and bragg	4. Spectral correlation

- 106. Fourier transform operates in which of the following domain
  - 1. Chromacity Plot
  - 2. Band spectral scatter Plot
  - 3. Frequency spectrum
  - 4. Spatial domain
- 107. How many different shades of grey are there in a colour RGB system in which each RGB image is an 7-bit image?
  - 1. 256
  - 2. 128
  - 3. 124
  - 4. 126
- 108. Which of the following index is generally used for yield forecast model?
  - 1. NDVI
  - 2. SAVI
  - 3. Soil brightness index
  - 4. NDWI
- 109. Separability of a image class depends on
  - 1. Image statistics
  - 2. The difference in spectral property of the image features at a particular band
  - 3. Number of training sites
  - 4. All the above
- 110. Histogram equalization increases the
  - 1. Color variations in the image
  - 2. The brightness of the image
  - 3. Color depth of the image
  - 4. Resolution of the image

- 111. When doing a linear contrast stretch, the count of unique digital numbers in a band
  - 1. Increases
  - 2. Increases but limited to 255
  - 3. Does not change
  - 4. None of the above
- 112. Which one of the following crop shows improved crop separability in SWIR?
  - 1. Gram
  - 2. Banana
  - 3. Sugarcane
  - 4. Rice
- 113. Identify the method which is not used earlier to compile forest information
  - 1. Panchromatic
  - 2. B and W IR
  - 3. CIR photographs
  - 4. Visual spotting
- 114. Dense forest contain crown cover of
  - 1. <40%
  - 2. >40%
  - 3. 10%-40%
  - 4. <10%
- 115. Land and Water can be easily distinguished in the region of
  - 1. Infra red
  - 2. Middle infrared
  - 3. Near infrared
  - 4. None of the above